

Challenges and Practical Solutions to Managing Municipal Stormwater Systems



Stories from the end of the pipe

Project Partners



- City of Dover, NH Staff
- UNH Stormwater Center
- NH Department of Environmental Services
- Environmental Protection Agency, Region 1



Berry Brook Watershed Management Plan –Implementation Projects Phase III



Final Report to
The New Hampshire Department of Environmental Services
Submitted by
The City of Dover and the UNH Stormwater Center
December, 2017



UNIVERSITY OF NEW HAMPSHIRE
STORMWATER CENTER



Berry Brook BMPS

0 0.0450.09 0.18 0.27 0.36
Miles

Legend

New BMPs

 BB_Watershed

2015 1-foot Orthophotography

BMPs

Installations include:

- 12 bioretention systems,
- a tree filter,
- a subsurface gravel wetland,
- one acre of new wetland,
- daylighted and restored 1,100 linear feet of stream at the headwaters and restored 500 linear feet of stream at the confluence including two new geomorphically-designed stream crossings
- 3 grass-lined swales
- 2 subsurface gravel filters
- an infiltration trench system
- 3 innovative filtering catch basin designs

Funding and Results



Funding: 3 watershed assistance grants (sec 319) and 1 aquatic resource mitigation grant, all with min 40% match from the city.

Berry Brook Project: Getting to 10%	
Cost	\$1,322,000
Grant Funds	\$793,000
Match (min estimate)	529,000
BMPs	26
DCIA Reduced	37 acres
TSS Reductions (lb./yr.)	57,223
TP Reductions (lb./yr.)	201
TN Reductions (lb./yr.)	1,127

Typical Project Approach



Develop a watershed management plan (a-i)

Optimize placement of BMPs for maximum gain

Implement

Model

Outreach and education on project results

Report

Typical Project Approach



2011 Watershed Restoration Grants for Impaired Waters

Section B: PRE-PROPOSAL APPLICATION FORM Watershed Restoration Grants for Impaired Waters


I. Proposal Title

Berry Brook Watershed Restoration through Low Impact Development Retrofits in an Urban Environment

II. Contact Information

Primary contact person: Dean Peschel
Organization: Environmental Project Manager, City of Dover DPW
Street address: 288 Central Avenue
City, State, ZIP: Dover, NH, 03820-4169
Day phone: (603) 516-6094 Fax: () Email: dean.peschel@ci.dover.nh.us

Secondary contact person: Robert M. Roseen, Ph.D., D.WRE, P.E.
Organization: Director, The UNH Stormwater Center
Street address: 35 Colovos Road
City, State, ZIP: Durham, NH, 03824
Day phone: (603)862-4024 Fax: (603)862-3957 Email: robert.roseen@unh.edu

Signature of Applicant: 

Date of signature: 9/2/10

III. Project Summary

Berry Brook is a highly urbanized 1st order stream located in Dover, NH, that is classified as Class B waters. . The Brook is located in a built-out, 164-acre watershed with 25% impervious cover (IC) and includes medium-density housing with commercial and industrial uses. The stream has been placed on the NHDES 2006 Section 303(d) list and is impaired for primary recreation and for aquatic life. The source of this impairment includes urbanization resulting in an increase of pollutant mass and runoff volumes from stormwater.

Optimize Again...

And then you implement – Inside a historic 40,000 sf slow sand filter



National Historic Preservation Act Section 106 Compliance for the Regulatory Program

Reality

Redesign

Reconfigure

**... and
optimize**


Again...



And more implementation...



Innovation Decision Process



Ability to reinvent to reflect local needs and foster ownership

Rogers, 2003

The tale of two raingardens ...







And more adaptation...NDP!



Maintenance Must be Included in the Design Process

Not by the designers, but by the people who are expected to do it and pay for it



Decadal Reflections: Cart Before the Horse

The expression cart before the horse is an idiom or proverb used to suggest something is done contrary to a conventional or culturally expected order or relationship.



“Bioretention Design”

381,000 results!

GOOGLE

bioretention design



All

Images

Shopping

Videos

News

More

Settings

Tools

About 381,000 results (0.33 seconds)

Images for bioretention design



→ More images for bioretention design

Report images

Bioretention Design Specifications and Criteria

www.leesburgva.gov/home/showdocument?id=5057

Bioretention is flexible in design, affording many opportunities for the designer to be creative. This design guide first goes into a step by step process of how to size and design bioretention to accommodate the design storm runoff amount. After that, how to integrate the bioretention facility(ies) into the overall site design is ...

Bioretention Manual - CT.gov

www.ct.gov/deep/lib/deep/p2/raingardens/bioretention_manual_2009_version.pdf

Mar 6, 2013 - This manual has been prepared to replace and update the 1993 edition of the Design Manual for Use of Bioretention in Stormwater Management. This manual builds on that work and further identifies methodologies, practices, and examples of bioretention. Changes that were made focus primarily on four ...


Designing Bioretention Areas

<https://www.unce.unr.edu/programs/sites/nemo/files/.../DesigningBioretentionAreas.pdf>

"Bioretention is the process in which contaminants and sedimentation are removed from stormwater runoff. Stormwater is collected into the treatment area which consists of a series of buffer strips, vegetated swales, and/or basins. The treatment area is designed to filter and ...


Comparison of Pollutant Removal Efficiency Planted vs Grassed Bioretention























■ Planted Bio (Avg. 3) ■ Grassed Bio




Grassed vs Planted Surface IR

Average Infiltration Rates of a Planted (blue) versus Grassed (green) Bioretention Systems Over Time



KEY	QUANTITY	NAME
	50	TUSSOCK SEDGE (<i>Carex stricta</i>)
	75	COMMON RUSH (<i>Juncus effusus</i>)
	350	SWITCHGRASS (<i>Panicum virgatum</i>)
	15	BLUE FLAB (<i>Iris versicolor</i>)
	50	JOE PYE WEED (<i>Eupatorium maculatum</i>)
	20	BLUE CARDINAL FLOWER (<i>Lobelia siphilitica</i>)
	100	FOX SEDGE (<i>Carex vulpinoidea</i>)
	15	NEW YORK ASTER (<i>Aster novi-belgii</i>)
	20	NEW YORK ASTER (<i>Aster novi-belgii</i>)
	40	BLUE CARDINAL FLOWER (<i>Lobelia siphilitica</i>)
	50	NEW YORK IRONWEED (<i>Vernonia noveboracensis</i>)
	50	NEW ENGLAND ASTER (<i>Aster novae-angliae</i>)
	150	BITTER PANICGRASS (<i>Panicum amarum</i>)
	40	BLUE CARDINAL FLOWER (<i>Lobelia siphilitica</i>)
	35	BLUE FLAB (<i>Iris versicolor</i>)
	75	COMMON RUSH (<i>Juncus effusus</i>)
	50	NEW YORK IRONWEED (<i>Vernonia noveboracensis</i>)
	15	NEW YORK ASTER (<i>Aster novi-belgii</i>)
	15	SWITCHGRASS (<i>Panicum virgatum</i>)
	20	BLUE CARDINAL FLOWER (<i>Lobelia siphilitica</i>)
	50	TUSSOCK SEDGE (<i>Carex stricta</i>)
	20	BLUE CARDINAL FLOWER (<i>Lobelia siphilitica</i>)

Traditional Approach



The Site Today



Add it to the toolbox!

Inevitably we need to
expand our toolbox

The more
SCMs/Modifications
/Innovations the
better

There is not a lot of
room for “turf”
battles!



Cart Before the Horse?

Are we focusing too much on modeling?

Are we focusing enough on implementation and adaptation?



Redesign

Reconfigure

... and

optimize

Again...

2013 Watershed Assistance Grants PROPOSAL FORM



**SUBMISSION
DEADLINE**



4:00pm
November 21, 2012

1. PROJECT TITLE

Getting to 10%: Watershed Restoration through Low Impact Development Retrofits in an Urban Environment

Berry Brook/Cocheco River Watershed Management Plan Implementation Phase III.

2. PROJECT LOCATION

A. Town(s): **Dover, NH**

Does project involve other states? Yes No

B. What water body does it affect? **Berry Brook/Cocheco River/Great Bay**

12-digit hydrologic unit code (HUC): 010600030608

C. Attach a project location map showing the watershed and relevant project site locations (required).

HUC look-up:
<http://www2.des.nh.gov/SWQA/> or
contact your DES project leader for
assistance.

3. GRANT CATEGORY

Please check applicable water quality category:

a. High Quality Waters

b. Impaired Waters

Please list the designated uses that are impaired and the specific causes of impairments as identified on the 2010 305(b)/ 303(d) Surface Water Quality Assessment. If the waterbody is not listed as impaired in the 2010 Surface Water Quality Assessment, then describe and attach documentation of the impairment.

2010 Surface Water Quality
Assessment:
[http://des.nh.gov/organization/divisions/
water/wmb/swqa/2010/index.htm](http://des.nh.gov/organization/divisions/water/wmb/swqa/2010/index.htm)

Primary Contact Recreation (as a result of high bacteria concentrations) and for Aquatic Life Use due to an NHDES assessment of benthic macroinvertebrate monitoring.

Results



Not one single installation was installed as originally planned

The entire project required flexibility in relation to all BMPs installed

Overall goals of the project (disconnection of EIC) was considered paramount objective over actual implementation sites.

Are we at the Finish Line or the Starting Line?



If necessity is the mother of invention?...

NECESSITY IS
THE MOTHER
OF INVENTION.


PLATO

Need for Innovation

- “Boulanginator” (subsurface gravel filter) mimics performance of PA with regular pavement.
- The hydraulic inlet and outlets are controlled through perforated pipes and underdrains.
- treat runoff from 1.96 acres and 0.61 acres DCIA




Boulangenator Performance



Need for Innovation

- In HSG A installed an infiltration trench between two conv CBs
- A simple but effective adaptation instead of solid pipe.
- Treats runoff from 3.36 acres and 1.04 acres DCIA




Modeled Performance



Infiltration Trench (2.41 in/hr) BMP Performance Table

BMP Capacity: Depth of Runoff Treated from Impervious Area (inches)	0.1
Runoff Volume Reduction	34%
Cumulative Phosphorus Load Reduction	33%
Cumulative Nitrogen Load Reduction	64%
Cumulative TSS Load Reduction	50%
Cumulative Zinc Phosphorus Load Reduction	81%

Hillcrest IT Performance



SGWS Costs



Site Characteristics and System Treatment Capacity						Annual Removals (lbs/yr)		
Project	Impervious Area (sf)	Impervious Area (acres)	Best Management Practice	Hydrologic Soil Group	Depth of Runoff Treated from Impervious Area (in)	Total Suspended Sediment	Total Phosphorus	Total Nitrogen
Hillcrest IT	39,640	0.91	Infiltration Trench	B	0.10	97	0.35	8.8

	Hillcrest IT
<u>Water Quality Volume</u>	IT
Drainage Area (ft ²)	39,640
% Impervious Cover	100%
Impervious Area (ft ²)	39,640
Conv WQV (ft ³) (@ P = 1.0in)	3,303
System Treatment	
System Area (ft ²)	10
Reservior Storage (ft ³)	400
System Storage (ft ³)	320
Rainfall Depth Treated (in)	0.10

Marginal Extra Materials


700 cf stone

Marginal Cost Difference

\$10,000

Need for Innovation

Sectional Media Box Filter Design – version 3




The Contractor shall verify and be responsible for all dimensions. DO NOT scale the drawing - any errors or omissions shall be reported to UNHSC without delay. The Copyrights to all designs and drawings are the property of UNHSC. Reproduction or use for any purpose other than that authorized by UNHSC is forbidden.



University of New Hampshire
36 Calovos Road
Durham, NH 03824
Phone: (603) 862-2819
Fax: (603) 862-3957
<http://www.unh.edu/unhsc>

No.	Date	Revision	Designed	Checked	Approved
1			TAP	JRH	



Project: **MEDIA BOX FILTER**
DOVER, NH

Date: June 7, 2018
Sheet No. 1 of 1

August 2017



- **Filtering Catch Basin Designed to replace conv DSCB where applicable**
- **This system was the third iteration**
- **The City has purchased four additional filtering catch basins and will install them in other areas throughout the city.**
- **The system is designed to treat 0.5 acres (0.25 acres/section) of IC per section and costs 2,400 per**













In Operation



Update May 2018





Update May 2018



Update May 2018





Innovations in water resource management: A common social responsibility



Conceptual Model Factors Influencing Adoption





Simplified Solution Model



■ Technical ■ Social ■ Situational

Case Study Score vs # BMPs





New Project Approach



Desktop designs invariably change when in-depth site specific investigations begin.

Better to quickly and coarsely develop a handful of candidate sites

Conduct inexpensive site queries of local areas of concern to further develop a practical mitigation approach.

Implement where and however much feasible

municipal implementation efforts adapt or innovate “text book” research-based designs with what is practical for a public works department working in an urban setting leading to lower costs and more effective systems.

New Project Approach



Large Project approach vs. every day counts approach

For the largest seacoast community there is:

- **Over 2800 catch basins**
- **65 linear miles of pipes**
- **200 outfall locations**

When all this infrastructure was originally designed the approach was very different.

Correction is not going to happen overnight!

Part of the Solution – Watershed approach all communities can access




<https://www.unh.edu/unhsc/berry-brook-project>




Berry Brook


EIC Reduction Target Rates for Berry Brook, Dover, NH



Hydrology




Direct Runoff Vs Rainfall Depth (Station/Downstream)




Modeled Water Quality


Mass Pollutant Export (lbs)



Mass Pollutant Export (lbs)



Mass Pollutant Export (lbs)



Results for Berry Brook at Station Drive







1-Inch Storm, $I_a = 0.05 S^1$

Year	% IC	P (in)	Q (in)	S (in)	CN	Q Reduction
2011	30	1.00	0.153	3.59	74	
2012	20	1.00	0.084	5.54	64	45.3%
2015	14	1.00	0.055	7.02	59	64.0%

³Hawkins, R.H.; Jiang, R.; Woodward, D.E.; Hjelmfelt, A.T.; Van Mullem, J.A. (2002).
"Runoff Curve Number Method: Examination of the Initial Abstraction Ratio".

27


Year	A	P	CN	TSS (lbs)	TP (lbs)	TN (lbs)
2008-20011	185	56.14	74	92,719	188	2,428
20012-2016	185	42.20	62	27,575	38	1,762
Annual Reductions (lb./yr.)				65,144	149	667
Simple Method (lb./yr.)				57,223	201	1,127



		TSS (mg/l) / (in)			Zinc (mg/l) / (in)			Nitrate-N (mg/l) / (in)			Total Nitrogen (mg/l) / (in)			Total Phosphorus (mg/l) / (in)		
		Pre	Mid	Post	Pre	Mid	Post	Pre	Mid	Post	Pre	Mid	Post	Pre	Mid	Post
Roosevelt	Weighted EMC	704	167	60	0.07	0.04	0.02	1.1	0.8	0.1	6.5	7.9	0.7	1.31	0.42	0.06
	% Difference		123%	168%		56%	121%		29%	161%		-20%	160%		104%	182%
Station	Weighted EMC	167	69	85	0.07	0.04	0.03	1.1	1.3	0.2	4.1	4.8	0.9	0.33	0.08	0.17
	% Difference		83%	65%		56%	84%		-12%	144%		-16%	127%		120%	65%
Average % Difference			103%	117%		56%	103%		8%	152%		-18%	144%		112%	124%



Temperature Data



One degree day is a day when the average stream temperature is one degree Fahrenheit above 65 degrees F. This is important as the temperature that a Brook Trout begins to feel heat stress is 65 °F. Therefore a day with an average daily stream temperature of 71 degrees would represent 6 degree days.

End? More Cart Before the Horse?

Are we inadvertently modeling optimized system performance ahead of long term operation and maintenance?



Operation and Maintenance






UNIVERSITY OF NEW HAMPSHIRE
STORMWATER CENTER






System Performance




TREE FILTER PERFORMANCE



Median Annual Influent Event Mean Concentrations (EMC) in mg/L

UNHSC	31	631	0.04	0.2	1.3	0.07
Ports TBF	39	520	0.10	0.2	1.5	0.21



Maintenance Basics



Pipe
from
in

ter
pts

Maintenance Basics




Pick
the
ma

rd
ny
ling.



Maintenance Basics

GI Vs Conv St Drainage Outfall Monitoring













End? More Cart Before the Horse?

Stormwater Modeling


Do we know what we are doing?



Yes, climate change gives us pause to think, but IC is the 800-pound gorilla




Design Dimensionless Hyetographs



Sampling of Observed Hyetographs

Durham, NH NOAA Gage



Sizing for Performance



Sizing Details



System	WQV ft ³ (m ³)	Actual WQV ft ³ (m ³)	% of normal design	Rain Event in (mm)	Sizing Method
SGWSC	7,577 (214.6)	720 (20.4)	10%	0.10 (2.5)	Static
IBSCS	1,336 (37.8)	310 (8.8)	23%	0.23 (5.8)	Dynamic

$$WQV = \left(\frac{P}{12}\right) \times IA$$

Static SGW System Sizing


Dynamic Bioretention Sizing

$$Af = Vwq * \frac{df}{(i(hf + df)tf)}$$


$$Q = CdA\sqrt{2gh}$$




Oyster River Road Cumulative Distribution Frequency




Durham Bio-5 Cumulative Distribution Frequency



Subsurface Gravel Wetland Performance



Biofiltration Performance



Design Storage Volume (DSV) - runoff depth from IA (in)

Analyte	Depth txt	Modeled RE	Measured RE
TSS	0.1	48	75
TZn	0.1	57	75
TN	0.1	55	23
TP	0.1	19	53

Analyte	Depth txt	Modeled RE	Measured RE
TSS	0.23	70	81
TZn	0.23	88	86
TN	0.23	60	27
TP	0.23	35	45

Region 1 GI Cost Estimates



BMP (From Opti-Tool)	Cost (\$/ft ³) ¹	Cost (\$/ft ³) – 2016 dollars ⁶
Bioretention (Includes rain garden)	13.37 ^{2,4}	15.46
Dry Pond or detention basin	5.88 ^{2,4}	6.80
Enhanced Bioretention (aka-Bio-filtration Practice)	13.5 ^{2,3}	15.61
Infiltration Basin (or other Surface Infiltration Practice)	5.4 ^{2,3}	6.24
Infiltration Trench	10.8 ^{2,3}	12.49
Porous Pavement - Porous Asphalt Pavement	4.60 ^{2,4}	5.32
Porous Pavement - Pervious Concrete	15.63 ^{2,4}	18.07
Sand Filter	15.51 ^{2,4}	17.94
Gravel Wetland System (aka-subsurface gravel wetland)	7.59 ^{2,4}	8.78
Wet Pond or wet detention basin	5.88 ^{2,4}	6.80
Subsurface Infiltration/Detention System (aka-Infiltration Chamber)	54.54 ⁵	67.85

¹ Footnote: Includes 35% add on for design engineering and contingencies

<https://www.unh.edu/unhsc/news/ms4-tools>

<https://www3.epa.gov/region1/npdes/stormwater/ma/green-infrastructure-stormwater-bmp-cost-estimation.pdf>

GI Implementation Cost Comparisons



Costs per disconnected acre of IC			
	PA	NY	NH
Actual	\$250,000.00	\$320,000.00	\$30,000.00

An aerial photograph of a large reservoir, likely a dammed river, surrounded by dense forest with vibrant autumn foliage in shades of orange, yellow, and green. The water is dark blue with numerous white wakes from boats. A semi-transparent grey rectangular box is overlaid on the upper portion of the image, containing the text "Questions???".

Questions???