The Evolution of Drainage and Stormwater Assets in Maryland Kiona Leah, P.E.



Information development and sharing

Maryland Department of Transportation State Highway Administration MDOT SHA

12/17/2020



Inventory Timeline



Program Structure

Planning

Engineering

Data Management Inventory Inspections & Performance Rating Action Rating Remediation Work Orders Retrofit Design



Construction

As-Built Certification

Remediation Verification



Future Focus

Business Process

Improvements

Sharing

Research

Operations

Minor Maintenance Routine Maintenance Procedures

Planning Taking Information and Generating Data – THEN and NOW

- Initial Information
 - Design Plans
 - Reports
- Turns into Data as a SWM facility number (SWMFAC#)
 - Specifications
 - MOUs
 - Agreements
 - Effectiveness of Treatment
 - Removal Results

BAILEY CONSULTING BAILEY BA9 FARMOL COX SUITE ICO BAILTMORE,

Planning Taking Information and Generating Data – THEN and NOW

Additional Information

- Specifications
- MOUs
- Agreements
- Effectiveness of Treatment
- Removal Results

Retrofits and Enhancements

SWH Facility Status Tracking Application Abandan SWM FAC [Sec: 1, 2, 3, 4, 6] Abandan SWM FAC [Sec: 1, 2, 3, 4, 6] The Track Longing (retroph/abandon) for facility will be generated one application has been application Cher Not an application has been application for ARES Colspan="2">Colspan="2">Section 200 Not an application for facility will be generated one application for ARES The Test Stormwater Facility Information Antiget Status Charging Application Status Charging Facility Spark Balance ac. As of — Watershould Spark Balance ac. As of Watershould Spark Balance <td c<="" th=""></td>	
Abandon SWMRAC (Sec. 1, 2A, 3A, 4, 6) TE: Certificate for status change (ktraft/sbandon) for faility will be generated application has been approved by the following "Adamped SWM Asker Manger" Abandon SWMRAC (Sec. 1, 2A, 3A, 4, 6) TION 1- Basic Scormwater Facility Information Note: Network Status Changer (Status) Plan Review Discion (or NEE) Status Water Quality Bank Baince Infinitation Tench (H-1) Infinitation Infinitation Status Water Quality Bank Baince =c. As of	
All Markets Text (All Stress All Stress Al	
**BaingerStMM.AsserManger **SpingerBight Autors **SpingerBight Autors **SpingerBight Autors **SpingerBight Autors NOTE: Required Fields Indicated Stat Incomplete forms will be rejected CION 1 - Basic Stormwater Facility Information Stare Water Audity Bains Infiltration Trench (h1) Infiltration Trench (h1) State Water Audity Bains Infiltration Trench (h2) Infiltration Trench (h2) Water Audity Bains Infiltration Trench (h2) Infiltration Trench (h2) Water Audity Bains Infiltration Trench (h2) Infiltration Trench (h2) Partice Designation on Plain (h3)Whd1, SDD 4 etc): Infiltration Trench (h2) Infiltration Trench (h2) Pho Statu/Complexenses: Infiltration Trench (h2) Infiltration Trench (h2) Infiltration Trench (h2) Pho Statu/Complexenses: Infiltration Trench (h2) Infiltration Trench (h2) Infiltration Trench (h2) Pho Statu/Complexenses: Infiltration Trench (h2) Infiltration Trench (h2) Infiltration Trench (h2) Pho Statu/Complexenses: Infiltration Trench (h2) Infiltration Trench (h2) Infiltration Trench (h2) Pho Statu/Complexenses: Infiltration Trench (h2) Infiltration Trench (h2) Infiltration Trench (h2) Pho Statu/Complexenses: Infiltration Trench (h2) Infiltration Trench (h2) Infiltration Trench (h	
DUTE: Required Fields Indicated With Accounts will be rejected CTION 1 - Back Scormwater Facility Information Infiltration Trench (I-1) Stare Water Address: Infiltration Trench (I-1) Stare Water Address: Infiltration Trench (I-1) Facility Designation on Plan (SWMA:1, SSD-4 etc): Infiltration Trench (I-1) Facility Designation on Plan (SWMA:1, SSD-4 etc): Infiltration Trench (I-1) Facility Designation on Plan (SWMA:1, SSD-4 etc): Infiltration Trench (I-1) Facility Designation on Plan (SWMA:1, SSD-4 etc): Infiltration Trench (I-1) Facility Designation on Plan (SWMA:1, SSD-4 etc): Infiltration Trench (I-1) Owner Name: Infiltration Trench (I-1) Infiltration (Infiltration Infiltration Infiltratinfiltrati	
CTION 1 - Basic Stormwater Facility Information Stare Water Address: Stare Water Address: Pien Data (for movide original, all others, use current): Owner Name: Owner Nam	
stormwater racitly (vps: stormwater racitly (vps: the intrinsion (rench)(-1) Watershafd/Stram Use Delignation Watershafd/Stram Use Delignation Watershafd/Stram Use Delignation Watershafd/Stram Use Delignation Watershafd/Stram Use Delignation Markershafd/Stram Use Delignation Markershafd	
State Variando Lasgination ac. As of Available Water Quality Bank Balance ac. As of Available Water Quality Bank Balance ac. As of Facility Designation on Plan (SWM-1, ESD-4 etc): Phin Satus/Completaness: Plan Satus/Completaness:	
Watershinds Veser (Maily Sains Balance ac. As of Within Arport Zone? Facility Sains Balance Pain Day Editory Comparison on Plain (SWMAL, ESD-4 ecc): Plains Sains Balance Plain Day Editory Comparison on Plain (SWMAL, ESD-4 ecc): Image: Comparison on Plain (SWMAL, ESD-4 ecc): Plain Day Editory Comparison on Plain (SWMAL, ESD-4 ecc): Image: Comparison on Plain (SWMAL, ESD-4 ecc): Owner Adrass: — Previously Assigned SWMARC Number (required for retrofit/abandon/access permit retrofit): Image: Comparison on existing facility acc. TOTO 2 - Stormwater Facility Design Information Image: Comparison on existing facility, coordinate as needed with the prainage and SWM Assets Team to aquire the original SVM Asset Team to acu. 100 Volume Provided (XXX) ic. ic. 100 Volume Provided (XXX) ic. ic. 100 Volume Provided (XXX) ic. ic. <t< td=""></t<>	
Available water (Jabling Same Same) Sec. Na Or Facility Designation on Plan (SWM-1, ESD-4 etc): Plan Statu/Completeness: Plan Data (for removal/abandon provide original, all others, use current): Owner dd/smis: Previously Assigned SWMAFAC Number (required for retroft/abandon/sccess permit retroft): TOMOR 1 Amount of the second of	
Millin Join Lotter Failing Designition on Plain (SWM-1, ESD-4 etc); Plan Date (for memory/leandon provide original, all others, use current); Owner Vans; Owner Vans; Tread of Address; Previously Assigned SWMFAC Number (required for retrofit/sbandon/access permit retrofit); TOTOR 2 - Stormwater Facility Design Information Stormage Assisting Facility (NXR) Imperiodus Area to Facility (NXR) Imperiodus Area to Facility (NXR) Imperiodus Area to Facility (NXR) Ist, Carl and	
Pachty Designation on Family NVD4, EDU-4 EQ. Pina Status/Completeness Pina Status/Completeness Downer OSWMFAC Number (required for retrofit/abandon/access permit retrofit): TOTION 2 - Stormwater Facility Design Information TOTION 2 - Stormwater Facility Design Information Proposed/Original Proposed	
Plan Date (for movide original, all others, use current):	
All Devine of SWM Factors:	
Owner Name:	
Write ranker.	
Almpervious/assignes/SWIATC Number (required for retrofit/bandon/access permit retrofit): 13337 Previous/assignes/SWIATC Number (required for retrofit/bandon/access permit retrofit): 13337 CTION 2 - Scormwater Facility Design Information Impervious/assignes/SWIATC Number (required for retrofit/bandon/access permit retrofit): 13337 Almpervious Area to Facility (XXX) ac. ac. ac. Ill Drainge Area to Facility (XXX) ac. ac. ac. Ill Drainge Area to Facility (XXX) ac. ac. ac. Ill Drainge Area to Facility (XXX) ac. ac. ac. Ill Drainge Area to Facility (XXX) ac. ac. ac. Ill Drainge Area to Facility (XXX) ac. ac. ac. Ill Drainge Area to Facility (XXX) ac. ac. ac. Ill Drainge Area to Facility (XXX) ac. ac. ac. Ill Drainge Area to Facility (XXX) ac. ac. ac. ID rounde (XXX) cu-4t. cu-4t. cu-4t. ID Valuer Provided (XXX) cu-4t. cu-4t. cu-4t. ID Valuer Provided (XXX) ct-4t.	
Transparsies animinal number (name in net/only abandon/access permit retrotic): 130357 TION 2 - Stormwater Facility Design Information	
CTION 2 - Stormwater Facility Design Information SECTION 2.8 Proposed/Original Facility SECTION 2.8 Alternate Alimparvious Area to Facility (XXX) ac. ac. al imparvious Area to Facility (XXX) ac. ac. Tratsed ac. ac. If provided (XXX) cu-ft. cu-ft. Di Volume Provided (XXX) cu-ft. cu-ft. Di Volume Provided (XXX) cfs cfs Di Volume Provided (XXX)	
SECTION 2A Proposed/Original Facility SECTION 2B Alternate NOTE: for design information on existing facility.coordinate as needed with the Drainage and SVM Assets Team to aguine the original SVM	
Proposed/Original Facility Alternate Aimpenvious Area to Facility (DXR) ac. ac. all menvious Area Treated (DXO) ac. ac. (Imparvious Area Treated (DXO) ac. ac. (DValume Provided (DXO) cu-ft. cu-ft. (DValume Provided (DXO) cu-ft. cu-ft. (DValume Provided (DXO) cds cfs yr Pask Discharge (DXO) cfs cfs <td< td=""></td<>	
Facility Facility ac. ac. al Impandous Area to Facility (XXK) ac. al Dranage Xrea to Facility (XXK) ac. al Dranage Xrea to Facility (XXK) ac. al Comparison of Cality (XXK) ac. al Dranage Xrea to Facility (XXK) ac. al Comparison of Cality (XXK) ac. al Cality	
Impervious Area to Facility (XXX) ac. ac. ac. all prainage Area to Facility (XXX) ac. ac. all Drainage Area to Facility (XXX) ac. ac. all Drainage Area to Facility (XXX) ac. ac. Inspervious Area Tracted (XXX) ac. ac. O'Nolme Provided (XXX) cu-ft. cu-ft. O'Nolme Provided (XXX) cu-ft. cu-ft. O'Nolme Provided (XXX) cu-ft. cu-ft. O'Nolme Provided (XXX) cfs cfs O'Pak Discharge (XXX) cfs cfs O'No The Thoreaston (L w X x D) in ft in ft Dankment Hight (I/L/A fracessary) ft ft m(Thankment Heard Class in ft in ft co Trace in ft in ft	
all mperious Area to Facility (XXX) ac. ac. facility, coordinate as needed with the Drainage and solv (XXX) Treated ac. ac. ac. ac. Interview Area Treated (XXX) ac. ac. ac. ac. Virpanious Area Treated (XXX) ac. ac. ac. ac. Divolume Provided (XXX) cu-ft. cu-ft. cu-ft. cu-ft. Divolume Provided (XXX) cts cfs cfs cfs -// Pack Discharge (XXX) cfs cfs cf	
al Drainage Area to Facility (DXX) ac. ac. ac. brainage and SVM Assets Team to a guire the original SVM Asset Team to a sto a start or a sta	
Treated Imparious Area Treated (XXX) ac. acult VProvided (XXX) cu-ft. cu-ft. cu-ft. cu-ft. 100 Vulume Provided (XXX) cu-ft. cu-ft. cu-ft. cu-ft. 100 Vulume Provided (XXX) cfs cfs cfs cfs 200 Valume Provided (XXX) cfs cfs cfs cfs 200 Valume Provided (XXX) cfs cfs cfs cfs 200 Valume Provided (XXX) cfs cfs cfs cfs	
Imparious Area Treated (XXX) ac. ac. ac. complete this information Vimparious Area Treated (XXX) cu-ft. cu-ft	
/Provided (XXX0) cu-ft. cu-ft. D/Volume Provided (XXX0) cu-ft. cu-ft. 100 Volume Provided (XXX0) cu-ft. cu-ft. 100 Volume Provided (XXX0) cu-ft. cu-ft. Pask Discharge (XXX0) cfs cfs. y-P sek Discharge (XXX0) cfs cfs. grap Facility Ommersons (Lx W × D) in ft in ft. bankment Height (I/ViAf necessary) ft ft. ft ft. ft. m/Emanwent Heard Class in Filtering Facility = Media Top > Top	
DV Olume Provided (XX8) cu-ft. cu-ft. DV Olume Provided (XX8) cu-ft. cu-ft. r Pask Discharge (XX8) cfs cfs. yr Pask Discharge (XX8) cfs. cfs. yr Pask Discharge (XX8) cfs. cfs. urage Facility Dimensions (LV XX x0) in ft. in ft. bankment Height (IN/A fi necessary) ft. ft. to of impounded Water (IVA A fi necessary) ft. ft. rg/Emaskment Haard Class cs. provided Top > Top Large Facility = Media Top > Top cs. provided Top > Top	
DOV Volume Provided (XXX0) Cu-At. Cu-At. Pask Discharge (XXX0) cfs cfs oyr Pask Discharge (XXX0) cfs cfs bankmart Height (IV/Af necessary) tft tht ft ft targe Facility (Increasery) tft m/Emaskment Heart (Olass in the interprovided (Discover) 10 yr	
CPBak Discharge (XXX) Cfs Cfs Cfs VP Pak Discharge (XXX) Cfs Cfs Cfs Dyr Pak Discharge (XXX) Cfs Cfs Cfs Discharge (XXX) Cfs Cfs Cfs Dyr Pak Discharge (XXX) Cfs Cfs Cfs Dyr Pak Discharge (XXX) Cfs Cfs Cfs Dyr Pak Discharge (XXX) Inft Inft NOTE: Average Depth is Defined as follows Dyr Pak Discharge (XXX) ft ft ft Large Facility (pond)=Bottom >10 yr Filtering Facility = Media Top > Top Cfs Top Filtering Facility = Media Top > Top Cfs	
yr Peak Dicknarge (XXX) Cfs Cfs yr Peak Dicknarge (XXX) Cfs Cfs yrage Facility Dimensions (Lx W x D) in ft in ft NOTE: Average Depth is Defined as follows bankment Heght (I/\u00ed, fracessary) ft ft ft Linear Facility = Bottom > 10 yr r/Email Science ft ft ft ft Large Facility (pond) = Bottom > 10 yr r/Email Mean (March Mean Class ft ft ft Filtering Facility = Media Top > Top	
Dyr, Pael Olscharge (XXX) Cfs Cfs Cfs yrage Facility Dimensions (Lx W D) in ft in ft NOTE: Average Depth is Defined as follows bankment Height (IV/A finecessary) ft ft Linear Facility = Bottom > Top oth of Impounded Water (N/A if necessary) ft ft ft v(Temaskment Heigard Class Filtering Facility (pond) = Bottom > 10 yr r(Temaskment Heizard Class Filtering Facility = Media Top > Top	
Inf Inft Inft Inft Inft NDE: Average Depth Is Defined as follows bankment Height (IV/Af necessary) ft ft Incer Section >0 op Incer Section >0 op bankment Height (IV/Af necessary) ft ft Large Facility = Bottom >0 op Incer Section >0 op r/Embankment Hszard Class Filtering Facility = Media Top > Top	
Dankment Heght (I/\/ifnecssan/) ft ft ft Linear Facility = Bottom > Top for of mounded Water (I/\/ifnecssan/) ft ft Itarge Facility (I/ond) = Bottom > 10 yr m/Emankment Heard Class ft ft Filtering Facility = Media Top > Top	
th of Impounded Water (N/A fracessary) ft ft Large Facility (pond) = 0ottom > 10 yr m/Embankment Hazard Class Filtering Facility = Media Top > Top	
m/Embankment Hazard Class Filtering Facility = Media Top > Top	
Ice Type	
DL Credit ONLY Access Permit Applications may list N/A	
eline Facility ONLY Access Permit Applications may list N/A	
CTION 3 - Project Information	
Proposed/Original Altorate	
Facility Alternate	

Planning

SWM Facility Inventory and Inspections - THEN

BMP Inventory

- BMP ID Number
- In Stream
- Location
- Road Name
- Fence
- Dam

BMP Inspection

BMP ID Number

33 Inspection Parameters for Triennial

Debris

BMP INVENTORY FORM

Camment

Caloription Unique SXVIII Facility IDA Sidigii BIM Pinumber

constructed in U.S. Waters

ances associated w/ BM F

Ion of BM P

irol structure 10 numbe

/o he owner Initication ID Irea of the BIU P polygon

epage control exists

ib senzation weitex is is? Ib senzation weitdep in (1) Mitikation ikench widtin (10)

nilination, hen chileng in (n) CS-DNR haar, class, for the emban werall SIAM FAC comments

rear facility was designed Present status of the BM P Date facility was abandoned

Zyrpeak discharge oul of BMP (cts) 10yrpeak discharge oul of BMP (cts) 100yrpeak discharge oul of BMP (cts)

Link value to the MIETADATA table BMP within 4 mile radius of airfeid?

cadway to the BIUP

BMP number from other owner Driginal BMP number Naintained by SKA Enu. Compl. Div

Contract ID number Calegory of BM P type Description of the facility designation

Dom a In

- Inflow Conditions
- Vegetation
- Ponding
- Access
- Mowability
- Emergency Spillway
- Orifice
- left Riser
- Outfall
- Other inspection protocols for annual, as built and emergency inspections



Planning SWM Facility Inventory and Inspections – and NOW

Technology Now

- Customized Off the Shelf Solution
 - Use Tablet
 Technology
 - Survey 1-2-3, ArcCollector
 - Additional form configuration

P48AM Wed Sep 23	APDES Inventory WTB Edit Mat GPS location not available		Arcais 50 Arcais 50	May 123 BMP Inspection BMP Inspection aninary Items Configuration Dage Guide Stude on what constitut Stude on what	M merezia M merezia M marection Type M morection Type M morection Data M education M education M education M education M education M morection Data M education M morection Data M education M morection Data M morec	A WPD use only: A WPD	Remediation Other Verification Other	So Paters residented Not Rated So Not Rated So Not Rated
×		BMP I	nspection Fo	'n	Δ Ξ	Not Part of Design	access road and, if it exists, how well is it -	5 NotRated
			1 of 1		+	BMP Access [®] Scores the extence of a maintenue are optional but recommended.	3	
- Ii	BMP Inspection spection Type *	Criteria				Access Comment		
(Triennial	Inspection Light	Construction Verification	Remediation Verification	Other			
C	Design Subcategory							

Planning SWM Facility Inventory and Inspections – and NOW ArcGIS Survey123 BMP Inspection Form BMP Inspectio The year of this inspection. Only update if told by SHA Preliminary Items \odot 2020-2021 **Technology Now** Form Configuration Overall Photos hable Image Guide lide on what const New Features this on will display an expandable Photo Expand it to see Smart Photo Subject Description: Scores the overall condition of the BMP related to the physical presence of unwanted woody/leafy material, garbage accumulations, and sedimentation that possibly can block the outlet structure. Trash can block important parts of the facility like the inlets and outlets as well as take up valuable storage area. Requirements Standard photo subjects V Long Comment Fields • Embedded Image Guide Office tools for data management 3D Objects Desktor - Documents Download Music Picture

Planning SWM Facility Inventory and Inspections – and NOW

Technology Now

- Additional Support Data Gathering Tools
 - SWM Inspection Tracker
 - Tracker Dashboard
 - Access Point Tracker



Planning SWM Facility Inventory and Inspections – and NOW

Office tools for data management

- Iterative process to verify inspections against parameters
- Sync Inspections
- Validate Field Changes
- Submit for Review
- Connecting and
 Watermarking Photos
- ♦ QA/QC



Planning SWM Facility Inventory and Inspections – Training

MDOT SHA Staff Take Over

- Training Inspectors
 - Classroom
 - Field Experience
- Training Office Staff
 - Preparation
 - QA/QC and Data Management



Engineering Action Ratings – THEN and NOW

Inspection Photos and Reports

• eGIS Upgrades

Engineering

Remediation Work Order Design – THEN

Traditional Reporting and Needs

- BMP Maintenance Report
 - Based on additional field assessment once assigned
 - Location Map
 - Maintenance Work Order
 - Maintenance Plan
 - Cost Estimate
 - As Built Plans and Details
- Developed in approximately 16 manhours

Traditional Permit Requirements

- MDOT SHA General Permit Allowed
 - Clearing & Grubbing
 - Sediment Removal
 - Slope and Structural Repairs
 - Pipe Cleaning
 - Facility Dredging

Average Number of Facilities Maintained Annually ~100

Standardized Templates Include

- Based on additional field assessment once assigned
- Location Map
- Erosion/Sediment
 Control General Notes,
 Details, Sequence of
 Construction /
- Standard language for Sequence of Construction

Standardized Templates Include

- Erosion Sediment
 Control Exhibits
- Detailed Design Plan
 Blow Up

Standardized Te

- Remediatic
- Standard la Action Lists

emplates include				C. I. T. C. The
Figures			il.	
guage for Remediation				Inflow #2
NOTIFY THE REGIONAL ENVIRONMENTAL COORDINATOR (REC) IN WRITING OR BY TELEPHONE AT 410-365-0164 AT LEAST SEVEN (7) WORKING DAYS PRIOR TO THE PRE-CONSTRUCTION MEETING AND THE EROSON AND SEDIMERT CONTROL (SC) WHEN MEETINGS MAY BE COMBINED. INSTALL INCHIN PERMETER CONTROL AS ESPECIFIED, LATE SPECIFIED, WHEN PERMETER CONTROL AS ESPECIFIED, LATE SPECIFIED, WHEN PERMETER CONTROLS AND INSTALL PRIMETER CONTROLS, WHEN INLET PROTECTION IS SPECIFIED, INSTALL INCHIN PROTECTION. WHEN APPROPRIATE, THE FOLLOWING STEPS MAY BE PERFORMED CONCURRENTLY AND IN ANY LOGICAL ORDER FOR THE FIELD REMEDIATION ACTION LIST	TRUCTION SEAMLESS CONTINU OAA 3-DAY DRY WE MUSING METHOD SH ERT TO THE OUTHET ENT LADEN WATER I YWET POOL AREA, AN L DISTUBED AREAS, I SRARY STABILIZATION NITHE MEXT WORK D E AREA WILL NO LOW Original MDDT SHV		a Rise Str Str Str Str Str Str Str Str Str Str	r control r control r control
Action		Mai	ntenance Actions	
1. Access the site from SHA owned parking area.	Add comments here	5 FACILITY #: 120067	0	REMEDIATION EXCIPENDE NO. 1 - AERIAL WITH ACTION CALLOUTS
 Ensure Erosion and Sediment Control is performed as indicated in the Remediation Action Projects Sequence of Construction for BMDs and ESC exhibit consider in this work order prior to any construction work 	i		ſ	DRAWING NO. 1 OF 4 SHEET NO. 6 OF 11
Remove guardrail as described on the ESC Exhibit,				
4. Ensure SWM Facility Remediation Verification Steps are performed concurrently with the work specified.				
 Unclog Low Flow Orifice in riser structure and lower water level through the dewatering device per design details, if possible. If the dewatering valve does not work, a pump and associated hoses will be required. 				
6. Expose outfall pipes and repair as necessary, with the approval of the Engineer.				
7. Determine the elevation of the bottom of the SVM facility and compare to as built plans or record drawings, whichever is evaluable. White exposed of the Engineer, remove excinutised sections and decavate the top layer of soil up to 12 below the design bottom elevation. Notify the Engineer (remove excinded bottom of the SVM facility and compare to any solution) and the engineer of the SVM facility and introduced the engineer. The end of the SVM facility and the engineer of the engineer removes the elevation of the SVM facility and the engineer of the engineer removes the elevation of the Engineer Perform targrass erabling home or 705.				

Standardized Te

- Remediation
- Standard la Action Lists

emplates include				100		4	and a set
Figures			al al	2.5	A	AND DESCRIPTION OF THE OWNER OWNER OF THE OWNER OF THE OWNER OF THE OWNER OWNER OF THE OWNER	
guage for Remediation				1111	TOUTO T	w #2	and the second
NOTIFY THE REGIONAL ENVIRONMENTAL COORDINATOR (REC) IN WRITING OR BY TELEPHONE AT 412-355-0164 AT LEAST SEVEN (7) WORKING DAYS PRIOR TO THE PRE-CONSTRUCTION MEETING AND THE EDGOID AND SEDIMENT CONTROL (ESC) MEETING AND THE EDGOID AND SEDIMENT CONTROL (ESC) MEETING AND MEETINGS MAY BE COMBINED. INSTALL INCH PERMETER CONTROL (SC) WHEN SPECIFIED WHEN PERMETER CONTROL AS SECIFIED, LINSTALL INCH PERMETER CONTROL AS SECIFIED, MISTALL INCH PERMETER FORTOCON IS SPECIFIED, INSTALL MEET PROTECTION. WHEN APPROPRIATE, THE FOLLOWING STEPS MAY BE PERFORMED CONCURRENTLY AND IN ANY LOGICAL ORDER FOR THE FIELD REMEDIATION ACTION LIST	ISTRUCTION TES SEAMLESS CONTINU NOAA 3-DAY DRY WE KOM USING METHOD SPI VATER TO THE OUTRO SPI VATER TO THE OUTRO SPI MENT LADEN WATER I LITY WET POOL AREA, AM ALL DISTURBED AREAS, I MENT LADEN WATER I UTY WET POOL AREA, AM A DISTURBED AREAS, I MENT AND THE NET WORK D THE AREA WILL NO LON			s a b c c c c c c c c c c c c c		a nondocara R	
Action	Original Moor any		Maintenance	Actions			
Access the site from SHA owned parking area	Add comments here.	TABLED & ADDRESS		00100101			MDE/PRD XX-PR-XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX
 Ensure Erosion and Sediment Control is performed as indicated in the Remediation Action Projects Sequence of Construction for BMDs and ESC axhibit consider in his work order prior to any generalization under 	·	FAGE(11 #; 120067			UNE NO, TEACRAE WITH ACTION CALLOUTS		DRAWING NO. 1 OF 4 SHEET NO. 8 OF 16
Remove guardrail as described on the ESC Exhibit.							
4. Ensure SWM Facility Remediation Verification Steps are performed concurrently with the work specified.				1			
 Unclog Low Flow Ortfloe in riser structure and lower water level through the dewatering device per design details if possible. If the dewatering valve does not work, a pump and associated hoses will be required. 							
6 Evenes outfail nines and repair as necessary with the anomal of the Epoineer				1			
 Expose versal pipes and repair as necessary, with the approval of the Engineer. 				1			
The Leaguest volume speed that report as introduced report of the Engineer. To elements Determine the elevation of the bottion of the SVM facility and compare to as built plans or record drawings, whichever is evaluable. With the approval of the Engineer, remove accumulated sediment and debris, and executed the top bayer of orall to to 12 'zaken's the design tottom elevation. Netly the Engineer if groundweth is encountered. Scartly the executed bottom of the SVM facility and compared to the signal compared							

Standardized Templates In

- As Built Plans
- Remediation Verification Fo

Maintenance of Traffic

nclude		STOR PURPOSE To affirm th NOTE Two (2) doctu remediation Perform Actio	MWATER MANAGEMENT (SWM) FA trough visual documentation the satisfactory completion of SWM facility remediation as spec will be approved.	
Form		DIRECTIONS Provide at least as follows:	Swin faithy remediation action List during impection and clearly show the construction action last inplotion of what appears in the photographic checklist on the same-day of completion of trends one (1) photographs and locations for each pertinent for ACCEMMENT (SWM) FACILITY	tand 2) SWA facility remediation weither the Engineer.
STORMWAT	rer i	MAN	PHOTO CHECK	LIST <u>MOT GENERAL NOTES</u> 1. ALL STANDARD REGULATORY AND WARNING SIGNS USED FOR MAINTENANCE OF TRAFFIC SHALL BE IN ACCORDANCE SIGN BOOK, IT SHALL BOOK, SIGN BOOK,
Note: A photograph is r	equired f	or all BOLD) features.	SUPPLEMENTS OF EACH OF THESE PUBLICATIONS FOR HIS USE ALL REGULATORY AND MARYLAND STANDARD "STANDARD SIZE", UNLESS OTHERWISE NOTED ON THE COPY AND WARNING SIGNS STAND AND "THE COPY AND WARNING SIGNS STAND AND WARNING STANDARD
Foature	Sta	tus	Comment	2. ALL TRAFFIC CONTROL DEVICES MUST ADHERE TO THE SUB DIRECTED BY THE ENGINEER.
OVERALL		Complete		ADMINISTRATION (AS AN ADMINISTRATION (AS AN ADMINISTRATION OF THE CURRENT EDITION OF THE MARYLAND MANUAL CHUR
BMP-Veg		Complete		EDITION OF THE MUSTAN BOOK OF STANDARDS FOR EDITION OF THE MARYLAND STATE MANDALA UNIFORM
(vegetation)		Complete		3. NO WORKING AND PEDESTRUCTION AND SPELIFICATIONS FOR CONSTRUCTION AND THE CURRENT
PRETREAT (Forebay/Pretreatment Area)		N/A		MARKINGS ARE IN PLACE AND OPERATIONAL ALL THE TEMPORARY TRAFED CONTROL AND PAVEMENT
		Complete		ENGINEER, SIGNS SHALL BE MOUNTED ON WOOD DOOD OF CONSTRUCTION, UNLESS OTHER MOUNTED SIGNS THAT ARE INSTALLED NEW CONSTRUCTION
EMBU				4. LONGITUDINAL DISTANCE OF USING FUSION SHALL HAVE RETRO REFLECTIVE SHOP OF USING STATE OF USING STATE OF USING
(Upstream cintouristication)		N/A		DRIVEWAYS, AND/OR FIELD CONTINUES WARNING SIGNS MAY BE AD ILITED BILLET
EMBD		Compiete		TEMPORARY SIGNING FOR LANE CLOSURES LANE SUCCESSION OF THE ENGINEER. WHERE ADVANCE STREETS, THE ADVANCE STREETS, T
(Downstream Embankment)		N/A		5. THE CONTRACTOR
OBE		Complete		RESTRICTIONS AND FERRID SECTION 104.01 OF THE CONTRACT OF THE
(Orifice Opening)		N/A		6 WHERE THE ORACY LANS AND SHOULDER CLOSURE SCHEDULE. DRIVENONS, FOR WORK HOUR DRIVENONS, 2 OF 4 SPEETING, 7 OF 19
		Complete		GRINDING OR HYDDON ACTION MARKING SARE REQUIRED EXPERIMENT
QIN (Inflows- All)				EXISTING PAVEMENT MARKINGS SHALL WITHIN THE LIMITS OF RESUBATIONS OF MARKINGS SHALL BE REMOVED BY
RSR		Complete		7. EXISTING SIGNE THE COVERED WITH BLACKOUT TAPE WHERE NEFFECTIVE
(Riser)		N/A		NON-TRANSPARENT MATERIAL SCHLER TRAFFIC PATTERING SUMMER
101101		Complet	e	RETURNING THE ROAD TO PRE-CONSTRUCTION TOWERD DURING CONSTRUCTION SHALL BE COVERED WITH A BLACK
PRIN_SPWY				8. ACCESS TO DRIVEWAYS AND STORE THAT IC. STORE STALL BE UNCOVERED PRIOR TO
(Designed runding standing		N/A Complet	te	THE PROPERTY OWNER (FOR THE FORMER OD BE MAINTAINED AT ALL TIMES UNLESS T
EMER_SPWAY		complet		MAINTAINED AT ALL TIMES TO ALL DRIVEWAYS ADDOUDED FOR THE LATTER I RARE PERMITTED BY
(Emergency Spillway)		N/A		A DECLARATE ACCESS POINTS.
O OUT DOWN		Comple	te	3. WHERE MOT SETUPS ARE PERMITTED DURING BEAK HOUSE
(Outfall - view downstream)		Comple	ste	DURING OF THE CONSTRUCTION PLASM HOURS, THE MOT SETUPS ARE TO REMAIN INSTALLED FOR THE
Q-OUT UP		Comple		NORTH HOURS SHALL BE DEFINED ACCORDING TO SECTIONE WORK IS TO BE COMPLETED
(Outfall - view upstream				IO SECTION 104 OF THE SPECIAL PROVISIONS.
Responsible Perso Responsible Perso	nnel Na onnel P.E	me Printe E. License	ed and Signature #	

Standardized Templates Include

- Appendix
 - Inspection Report
 - Photo Location Map
 - Inspection Photos
- Development Time 64 hours

Inspection Parameters for Work Orders

- Most frequently asked question during first inspection training
 - More in depth 93 parameters
 - Additional construction information
 - Smart Excel
- Plans for Additional Survey 123 and ArcCollector surveys

Engineering Remediation/Retrofit Tracking - THEN

Current Permit Requirements

- MDOT SHA General Permit Pending
 - Brush and Woody Vegetation Clearing only up to 4" DBH allowed
 - Sediment Removal
 - Pipe Cleaning
 - Facility Dredging

- Additional Permits needed for:
 - line JPA
 - Roadside Tree
 - AASCD
 - Critical Area
 - SLOA

	_			EPD Screening	Environmental			Severn	Permitting
IMP 🐺	BMP Type 🛛	Work Order Status 👻	Work Order Consulta -	Y/N -	Permits 🔹	Resources 🛛 👻	CAC	Watershed? 🔽	Authority -
	Infiltration Basin					DNR Sensitive			
	initiation basin	PRD aprroval under 17-PR-0194-17	Dewberry	Y	RTP	species	N	N	SHA PRD
						national wetlands			
						inventory (NWI),			
020013	Wet Pond					Forest interior			
						dwelling bird			
		Submitted to PRD under 17-PR-0194-03	Dewberry	y	JPA	species, FIDS	N	Y	
020026	infilmenting Toronth	Exempt from ESC approval, waiting for				DNR Sensitive			
020036	Infiltration Trench	RTP	RAM	Y	RTP	species	n	Y	SHA PRD
020083	Infiltration Trench	PRD aprroval under 17-PR-0194-17,	RAM	¥.	RTP, AASCD	n	n	Y	SHA PRD
020110	Wet Bread	Will be submitted to PRD under				local protected lands			
020110	wet Pond	17-PR-0194-04	Dewberry	y .	JPA	harmans park	n	N	
		Comments sent to Dewberry 3/19.							
	Bioretention	Waiting to finalize ESC Sequence to							
		proceed.	Dewberry	y .	n	n		N	
	Dry Pond	HHD received 11/13/17	WBCM	Y	maybe	n	n	N	
		Comments sent to Dewberry 3/19.							
020124	Wet Pond	Waiting to finalize ESC Sequence to							
		proceed.	Dewberry/Suyash	Y	maybe	NWI	n	N	
020143	Infiltration Trench	PRD aprroval under 17-PR-0194-17,	RAM	y .	RTP	n	n	N	SHA PRD

5 *	Facilities Maintained						
	2017	~8					
	2018	~4					
	2019	~37					
	2020	~4					

Engineering

Remediation/Retrofit Tracking - NOW

• Updated Permit Tracking for project development

46 Parameters

Construction

Contract Types – THEN and NOW

- Historically Many Types of Contracts have been used
 - Bid-Build
 - Design-Build
 - Memorandum of Understanding
 - Area Wide
 - Time and Materials
 - Bid Item

Routine and Minor Maintenance – Then and Now

Data Sharing with Maintenance Staff

- Provides Planning Opportunities
- Budget Decisions

SWM	
Condition	Totals
Routine	
Maintenance	5073
Minor	
Maintenance	1825
Remidiation	
Work Order	995
Retrofit/	
Enhancement	
Design	81
Reinspection	
Needed	82
Total	8,056

Cambridge

Princess Anne

Salisbury

Snow Hill

Centerville

Chestertown

Denton

Easton

Elkton

Fairland

Shop Name

Distric

1

1

2

2

2

2

2

3

Routine Maintenance Procedures – THEN and NOW

Received/Anticipated

October 2017

October 2017

September 2017

October 2017

October 2017

October 2017

October 2017

October 2017

April 2016

April 2016

Date Manual

SWM Facility Routine Maintenance Manuals

Physical Copies Provided

PDF and CDs Provided-

Available On-Line

3 Gaithersburg **April 2016** Stormwater Management Facility Routine Maintenance Manual April 2016 Laurel April 2016 Marlboro **Total Distributed to** 6 date Can be Found ON-LINE at:

https://www.roads.maryland.gov/Index.aspx?PageId=363

Annual Department Transformation

Sorting the Information in the Manual

- Types of SWM Facilities
 - Dry Pond
 - Wet Pond
 - Infiltration Facility
 - ♦ Filtration Facility
 - Bio-Swale
 - Turfgrass Facility–follow standard turfgrass maintenance guidelines

Dry Pond

- Should hold runoff temporarily and release fully. Generally, appears as a grass basin with no permanent pool of water.
- Verify facility is not holding water after 72 hours and report if found

Wet Pond

- Should hold a certain amount of runoff permanently. Generally, includes a grass embankment and unmowed 15-foot aquatic perimeter around a pool of water.
- Verify that pond drain opening in the riser is completely sealed

Infiltration Facility

- Should release runoff thru media in order to soak into the ground directly. These may be ditches or basins and have grass or stone bottoms with an observation well.
- Facility type very prone to clogs at outflows and leaf/sediment/debris build up at bottom

Bio-Swale

- Specific type of filtration facility located in a ditch. Generally, includes check dams along the length to create temporary ponding. Functionally similar to Dry Swales.
- Facility type very prone to clogs at outflows or underdrains and leaf/sediment/debris build up at bottom.

Filtration Facility

- Should release runoff thru a filter bed in order to be carried away by underdrains. Generally include cleanouts above the surface and may be fully vegetated or mulched
- Facility type very prone to clogs at outflows or underdrains and leaf/sediment/debris build up at bottom.

Operations

Routine Maintenance Procedures – NOW and SOON

Work Schedule Summaries

- Spring Maintenance
 - March 15-May 15
- Fall Maintenance
 - ♦ Sept. 15 Dec 15
- Work Description
- Needed Equipment and Materials
- Notes and Troubleshooting
- Common Problem List

ioc	
162	(c) wight
ring (March 15 - M	ay 15) Materia
Once each spring the	Equipment
A sing Maintenance WOR.	Fouipment
spring Work Items	cycli zick Up Truck
specific of devices as needed	chovel
1. Instant	Rake trook
a pemove waste including en structures.	Other Hand 1000
2. Kenne trash rack, riser and com	
to structures. Notify	
http://work is needed	Shovel
3. Check for determine Engineer Inter	Rake wand Tools
Resident Mainteen and Ing in the facility regetation that blocks	Other Trimmer
4. If water is still perclogs and clear to HHD.	String that
storm, cirecting Report excess porter	aigk-Up Truck
water not	as shovel
is used sediment from the factory	ost Rake uzods
Remove accumulated scale and low flow of the	Other Hand Tools Subsoil
around principle spinter	Shovel Cement
critical.	Rake Hand Tools Furnished Vol Alix
hurrows in embankments of a mud-	nipe Other Hand
6. Fill animal burrels subsoil and 1-part of diameter smooth	until smooth Pipe
using 9 parts 24-inch long 0 a tight fit. Pour sith subso	Silland Section (24" long
slurry. I want the hole with any opening with su	nd 6" diam)
full, then remove piper with 2 in. top	pressions, Herbicide
compact. Cover Lange. Report any Solice	Chain Saw Water
permanently store to HHD.	ight (DBII)
or water seep to with a diameter at or water 4.5 f	t, above
7. Remove trees the approxime per Lan	dscape
under 2 m. the touching the distance the	anzitable
highest grownt Guide (LMG). HHD to flag ac	Herbicide
Management coordination with the	Chain Saw Water
require the removal.	Backput Backput or Side
location brush and control prise	Articulate
8. Reffore (Zone 1) areas per LN	string Trimmer
Livio: Mow short meadow (2010 -)	pick-Up Truck
9. NOT	d disposal site.
Laicnose waste at approve	
10. Transport and dispose	
11. Remove MOT devices	

pecember 15) Materials
s fall (September 15 - Decempent
Once each lainter Equipments
Intenance Work: MOl/Jaujoment
Equip Equip And
want devices as needed
tall MOTshows debris from perShove
Rake Rake Rake Rake Rake Rake Rake Rake
emove wand other structures. Other Heroman
rash rack drift
ater at breast height to
trees with a diameter exyimately 4.5 ft, above
Remove the measured approximation of the second sec
under 2 m. touching the deviation with HnD to Herbicide
highest group 2 in, require color semoval.
larger than 2 he locations for terms wasive weeds per Lives Backpack Spire side
flag acceptable & control priority investigation and Articulated or Store
A. Remove brush Ceche Levina Facility (Zone 10) Arm Mower
string Trimmer Subsoil
5 Mow short measurer LMG. Shovel Furnished maximum for ass Seed Mix
meadow areas period
ort stone and geotextile with geotextile with Other Hand Year Type A Station Matting
6 Remove and reserve and depressions beneating the grades. Key in Stationary Statione
filling in ruts and depressions und depression
common borrounding full surrounding full set the original lines and Classification of the common set of the original lines and the common set of the common
geotextile and the ground to the
topsoil to reserve a seed sprease type and the stabilization Matting
grades
ad in bare soil a reads an additional addit
7. Apply seed in Matting per Livion
Stabilization pick-0pm
te at approved disposate
and dispose waste very the set of facility.
8. Transport devices.
9. Remove work in the shooting facility. Do not drive equipment. Place signs and other
Notes and Troubless damage soil of facinety and protective equipment
no not create ruts of the commended personal reasonal reasona
- Now guidelines for record and WZTC
scordance with MUTCP-
accuración Problems 6. Unstable Entre Angeling Water
1 Frosion mulation 7. Excess Pointers
a Sediment Accumulation
a Lack of Vegetation
Fxcessive Vegetation
4.

Routine Maintenance Procedures – NOW and SOON Identify and Solve Common Problems - Erosion

Very common problem especially along ditches or embankments. Can occur when soils are not properly compacted or vegetation doesn't establish. Small problems can become large if not treated quickly.

Problem	Solution
Minor Erosion	Fill eroded area with Furnished Topsoil as necessary to restore the original ground surface. If it is adjacent to existing rip rap, stabilize with Class I. Otherwise, re-seed with Turfgrass Seed Mix and Type 'A' Matting.
Major Erosion	Report to HHD

Routine Maintenance Procedures – NOW and SOON Identify and Solve Common Problems – Sediment Accumulation

 Sediment accumulation can be a major problem because it slows infiltration and other functions. If found sediment should be removed from forebays, outfalls and other areas around SWMFACs

Problem	Solution
Minor Sediment Accumulation	Remove minor sediment accumulated with a shovel. If necessary, re- seed the area with Turfgrass Seed Mix and Type 'A' Matting
Major Sediment Accumulation	Report to HHD

Identify and Solve Common Problems – Lack of Vegetation

Most commonly identified by areas of bare soil and is a problem because it leads to erosion

whi	Problem	Solution	s
cou	Small Area of Bare Soil	Re-seed the bare area with Turfgrass Seed Mix and Type 'A' Matting	
	Large Area of Bare Soil	Report to HHD	

Identify and Solve Common Problems – Excess Vegetation

• Excess vegetation causes major issues of blocking pipes, structures and weirs; interfering with filter media; interfering with inspection routes and access; and decreasing available storage volume.

Problem	Solution
Excess Vegetation	Clear the vegetation with a weed Trimmer

Identify and Solve Common Problems – Structure Damage

• Large debris, ice, soil settlement or other issues can cause damage to end structures, pipes, observation wells. Structure and pipe maintenance is important to ensure proper water collection and conveyance.

Problem	Solution
Damaged or deteriorated structure or pipe	Report to Resident Maintenance Engineer to determine how to repair

Operations

Routine Maintenance Procedures – NOW and SOON

Identify and Solve Common Problems – Unstable Embankment

• Failure of an embankment which holds water in the facility can result in water escaping in problematic ways and not managing flooding as needed. Identifying potential problems such as soft spots, depressions, seepage, erosion and holes is very important.

Problem	Solution
Animal Burrows or Other Holes	Mud-pack using 9 parts subsoil and 1 part cement in a mud-like slurry. Place a 24-inch long 6-in. diameter smooth pipe vertically into the hole with a tight fit. Pour slurry until full, then remove pipe. Tamp opening with subsoil and compact. Cover tamped area with 2 in. topsoil and permanently stabilize.
Minor Erosion	Fill eroded area with Furnished Topsoil as necessary to restore the original ground surface. If it is adjacent to existing rip rap, stabilize with Class I. Otherwise, re- seed with Turfgrass Seed Mix and Type 'A' Matting
Soft Spots, Depressions, Seepage or Other Problems	Report to HHD

Identify and Solve Common Problems – Excess Ponding

Except Wet Ponds, all other facilities should not have water visible 72 hours after a rain event. Ponding shows that outflow structures may be clogged; sediment or debris has clogged filter materials or underdrains are blocked. Even once resolved these issues should be reported to HHD.

Problem	Solution
Outflow Points are Clogged	Clear clogs in or obstruction to the outflow point(s)
Leaves/Sediment/D ebris has Accumulated in Facility Bottom	Remove minor leaf/sediment/debris buildup from the bottom of the facility. Report major buildup to HHD.
Underdrain is Blocked	Clean out the underdrain with a vacuum truck
Filter Media is Clogged or Compacted or Other Problem	Report to HHD

Future Focus

Business Process Improvements

New GIS Applications

- Much more overlaid information
 - Drainage Complaint Data
 - Crash Data from excess water
 - Property Information
 - TMDL Planning from OED
 - Soils Information
 - Watershed Boundaries
 - Roadway Projects
 - Contract Information
 - Sea Level Rise Investigations
 - Tree Conflict Studies

Future Focus

Business Process Improvements

- SWM Facility Inspection Tracker
 - Daily Live Progress Updates
 - Dashboard of Inspection Ratings
- Outfall Inspection Program
- Dam Inspection Program
- Video Pipe Inspection for Drainage Inspection
 - CMP Pipes are Aging and Failing and Disrupting our Roadway System.
 - A Proactive and Less Reactive Approach
- Water Quality Bank Tracking
 - Tracks amount of amounts of impervious managed or treated for WQ in acres

Sharing

More than JUST the Database

- New File Organization
 - Search Tools
 - Database Sharing Tools thru On-Line Platforms

Future Focus

Asset Management Expertise

Capital Needs SOGR Forecast: Drainage

Data strengths/gaps vary per sub-category

- a. SWMFAC Strong with few gaps and updated daily
- b. Drainage Medium with major gaps and updated annually
- *c. Outfalls* Medium with major gaps updated quarterly
- d. Dams Strong with few gaps and updated annually

All aspects require better maintenance tracking and operations training materials.

Future Focus

Asset Management Expertise

Contact Me

Kiona A. Leah, P.E.

kleah@mdot.Maryland.gov

410-545-8044

